640193-00 PAGE 1 OF 5

MOBIL OIL CORPORATION MATERIAL SAFETY DATA BULLETIN

REVISED: 06/19/92

MOBILTEMP 78

SUPPLIER:

24-HOUR EMERGENCY (CALL COLLECT):

(609) 737-4411

MOBIL OIL CORP.

CHEMTREC:

CHEMICAL NAMES AND SYNONYMS: PET. HYDROCARBONS AND ADDITIVES

(800) 424-9300

USE OR DESCRIPTION:

PRODUCT AND MSDS INFORMATION:

HIGH TEMPERATURE GREASE (800) 662-4525

APPEARANCE: GRAY-BLACK GREASE ODOR: MILD PH: NA VISCOSITY AT 100 F, SUS: 2448.0 AT 40 C, CS: 460.0 VISCOSITY AT 210 F, SUS: 155.0 AT 100 C, CS: 32.0 FLASH POINT F(C): > 400(204) (ESTIMATED (OIL COC)) MELTING POINT F(C): NA POUR POINT F(C): NA BOILING POINT F(C): > 600(316) RELATIVE DENSITY, 15/4 C: 0.9 SOLUBILITY IN WATER: NEGLIGIBLE VAPOR PRESSURE-MM HG 20C: < .1

NOTE: MOST PHYSICAL PROPERTIES FOR OIL COMPONENT.

NA=NOT APPLICABLE NE=NOT ESTABLISHED D=DECOMPOSES FOR FURTHER INFORMATION, CONTACT YOUR LOCAL MARKETING OFFICE.

# \$ # # # \$ # # # # # # # # # # # # # #	III. POTENT	ALLY HAZAI WT PCT (APPROX)	RDOUS INGRED EXPOSURE L MG/M3 _ 1	INITS SOURCES
MOLYBDENUM (IV) (1317-33-5)	SULFIDE	1	10 10	A-(AS MO-INSL) M-(AS MO-INSL)
(1317-33-3)			10	O-(AS MO-INSL)
GLYCERIN (56-81-	-5)	1	10	A-TOTAL DUST
			10	H
			10	O-TOTAL DUST
			5	O-RESP. FRACT.

SEE SECTIONS XII AND XIII FOR REGULATORY AND FURTHER COMPOSITIONAL DATA.

SOURCES: A=ACGIH-TLV, A\*=SUGGESTED-TLV, M=MOBIL, O=OSHA, S=SUPPLIER NOTE: LIMITS SHOWN FOR GUIDANCE ONLY. FOLLOW APPLICABLE REGULATIONS.

--- INCLUDES AGGRAVATED MEDICAL CONDITIONS, IF ESTABLISHED ---EFFECTS OF OVEREXPOSURE: NOT EXPECTED TO BE A PROBLEM.

EYE CONTACT: FLUSH THOROUGHLY WITH WATER. IF IRRITATION PERSISTS, CALL A PHYSICIAN.

SKIN CONTACT: WASH CONTACT AREAS WITH SOAP AND WATER. HIGH PRESSURE ACCIDENTAL INJECTION THROUGH THE SKIN REQUIRES IMMEDIATE MEDICAL ATTENTION FOR POSSIBLE INCISION, IRRIGATION AND/OR DEBRIDEMENT.

INHALATION: NOT EXPECTED TO BE A PROBLEM.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

INGESTION: NOT EXPECTED TO BE A PROBLEM. HOWEVER, IF GREATER THAN 1/2 LITER (PINT) INGESTED, IMMEDIATELY GIVE 1 TO 2 GLASSES OF WATER AND CALL A PHYSICIAN, HOSPITAL EMERGENCY ROOM OR POISON CONTROL CENTER FOR ASSISTANCE. DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

\*

FLASH POINT F(C): > 400(204) (ESTIMATED (OIL COC))

FLAMMABLE LIMITS. LEL: NE UEL: NE

EXTINGUISHING MEDIA: CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG.

SPECIAL FIRE FIGHTING PROCEDURES: WATER OR FOAM MAY CAUSE FROTHING.

USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE

USED TO FLUSH SPILLS AWAY FROM EXPOSURE. FOR FIRES IN ENCLOSED

AREAS, FIREFIGHTERS MUST USE SELF-CONTAINED BREATHING APPARATUS.

PREVENT RUNOFF FROM FIRE CONTROL OR DILUTION FROM ENTERING STREAMS,

SEWERS, OR DRINKING WATER SUPPLY.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE.
NFPA HAZARD ID: HEALTH: 0, FLAMMABILITY: 1, REACTIVITY: 0

\*

ENVIRONMENTAL IMPACT: REPORT SPILLS AS REQUIRED TO APPROPRIATE

AUTHORITIES. U. S. COAST GUARD REGULATIONS RÉQUIRE IMMEDIATE

REPORTING OF SPILLS THAT COULD REACH ANY WATERWAY INCLUDING

INTERMITTENT DRY CREEKS. REPORT SPILL TO COAST GUARD TOLL FREE

NUMBER (800) 424-8802. IN CASE OF ACCIDENT OR ROAD SPILL NOTIFY

CHEMIREC (800) 424-9300.

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED: ADSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, ETC. SHOVEL UP AND DISPOSE OF AT AN APPROPRIATE WASTE DISPOSAL FACILITY IN ACCORDANCE WITH CURRENT APPLICABLE LAWS AND REGULATIONS, AND PRODUCT CHARACTERISTICS AT TIME OF DISPOSAL.

WASTE MANAGEMENT: PRODUCT IS SUITABLE FOR BURNING IN AN ENCLOSED, CONTROLLED BURNER FOR FUEL VALUE OR DISPOSAL BY SUPERVISED INCINERATION. SUCH BURNING MAY BE LIMITED PURSUANT TO THE RESOURCE CONSERVATION AND RECOVERY ACT. IN ADDITION, THE PRODUCT IS SUITABLE FOR PROCESSING BY AN APPROVED RECYCLING FACILITY OR CAN BE DISPOSED OF AT ANY GOVERNMENT APPROVED WASTE DISPOSAL FACILITY. USE OF THESE METHODS IS SUBJECT TO USER COMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS AND CONSIDERATION OF PRODUCT CHARACTERISTICS AT TIME OF DISPOSAL.

## MOBILTEMP 78

\*
EYE PROTECTION: NO SPECIAL EQUIPMENT REQUIRED.

- SKIN PROTECTION: NO SPECIAL EQUIPMENT REQUIRED. HOWEVER, GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS BE FOLLOWED.
- RESPIRATORY PROTECTION: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.
- VENTILATION: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

- ORAL TOXICITY (RATS): LD50: > 5 G/KG O/10 RATS DIED AT THIS DOSAGE LEVEL. CONSIDERED TO BE NO MORE THAN SLIGHTLY TOXIC BASED ON SINGLE DOSE LEVEL TESTING AT 5 G/KG.
- DERMAL TOXICITY (RABBITS): LD50: > 2 G/KG O/10 RABBITS DIED AT THIS DOSAGE LEVEL. CONSIDERED TO BE NO MORE THAN SLIGHTLY TOXIC BASED ON SINGLE DOSE LEVEL TESTING AT 2 G/KG.
- INHALATION TOXICITY (RATS): NOT APPLICABLE ---HARMFUL CONCENTRATIONS OF MISTS AND/OR VAPORS ARE UNLIKELY TO BE ENCOUNTERED THROUGH ANY CUSTOMARY OR REASONABLY FORESEEABLE HANDLING, USE, OR MISUSE OF THIS PRODUCT.
- EYE IRRITATION (RABBITS): CAUSED NO SIGNIFICANT IRRITATION TO RABBITS.

  EYE IRRITATION SCORES: O AT 24 HOURS, O AT 48 HOURS, O AT 72 HOURS

  SKIN IRRITATION (RABBITS): NOT IRRITATING TO RABBITS AFTER 4 HOUR

  CLOSED PATCH CONTACT.
- ---SUBCHRONIC TOXICOLOGY (SUMMARY)--SEVERELY SOLVENT REFINED AND SEVERELY HYDROTREATED MINERAL BASE OILS
  HAVE BEEN TESTED AT MOBIL ENVIRONMENTAL AND HEALTH SCIENCES
  LABORATORY BY DERMAL APPLICATION TO RATS 5 DAYS/WEEK FOR 90 DAYS AT
  DOSES SIGNIFICANTLY HIGHER THAN THOSE EXPECTED DURING NORMAL
  INDUSTRIAL EXPOSURE. EXTENSIVE EVALUATIONS INCLUDING MICROSCOPIC
  EXAMINATION OF INTERNAL ORGANS AND CLINICAL CHEMISTRY OF BODY
  FLUIDS, SHOWED NO ADVERSE EFFECTS. DERMAL APPLICATION OF THIS
  PRODUCT AT DOSES UP TO 2000 MG/KG/DAY FOR 13 WEEKS TO MALE AND
  FEMALE RATS PRODUCED MINIMAL SKIN IRRITATION, AND VIRTUALLY NO
  SYSTEMIC TOXICITY.
- THE BASE OILS IN THIS PRODUCT ARE SEVERELY SOLVENT REFINED AND/OR SEVERELY HYDROTREATED. CHRONIC MOUSE SKIN PAINTING STUDIES OF SIMILAR OILS SHOWED NO EVIDENCE OF CARCINOGENIC EFFECTS. THIS MATERIAL IS NOT A SENSITIZER UNDER THE CONDITIONS OF THE BUHLER (GUINEA PIG) PATCH TEST.

\*

GOVERNMENTAL INVENTORY STATUS: ALL COMPONENTS REGISTERED IN ACCORDANCE WITH TSCA.

DOT:

SHIPPING NAME: NOT APPLICABLE HAZARD CLASS: NOT APPLICABLE

US OSHA HAZARD COMMUNICATION STANDARD: PRODUCT ASSESSED IN ACCORDANCE WITH OSHA 29 CFR 1910.1200 AND DETERMINED NOT TO BE HAZARDOUS.

RCRA INFORMATION: THE UNUSED PRODUCT, IN OUR OPINION, IS NOT SPECIFICALLY LISTED BY THE EPA AS A HAZARDOUS WASTE (40 CFR, PART 261D), NOR IS IT FORMULATED TO CONTAIN MATERIALS WHICH ARE LISTED HAZARDOUS WASTES. IT DOES NOT EXHIBIT THE HAZARDOUS CHARACTERISTICS OF IGNITABILITY, CORROSIVITY, OR REACTIVITY AND IS NOT FORMULATED WITH CONTAMINANTS AS DETERMINED BY THE TOXICITY CHARACTERISTIC LEACHING PROCEDURE (TCLP). HOWEVER, USED PRODUCT MAY BE REGULATED.

THIS PRODUCT HAS BEEN AUTHORIZED BY USDA FOR USE UNDER THE FOLLOWING CATEGORY: H2 - LUBRICANTS WITH NO FOOD CONTACT

U.S. SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) TITLE III: THIS PRODUCT CONTAINS NO "EXTREMELY HAZARDOUS SUBSTANCES".

SARA (311/312 - FORMERLY 302) REPORTABLE HAZARD CATEGORIES: NONE

THIS PRODUCT CONTAINS NO CHEMICALS REPORTABLE UNDER SARA (313) TOXIC RELEASE PROGRAM.

THE FOLLOWING PRODUCT INGREDIENTS ARE CITED ON THE LISTS BELOW:

CHEMICAL NAME	CAS NUMBER	LIST CITATIONS
1,2,3-PROPANETRIOL	56-81-5	1, 2, 7, 8, 11, 17
ZINC (ELEMENTAL ANALYSIS) (.03%)	7440-66-6	15
ZINC, BIS (DIPENTYLCARBAMODITHIOATO-	15337-18-5	15
(5,5)-, (T-4)- (.25%)		
QUATERNARY AMMONIUM COMPOUNDS,	68953-58-2	15
BIS (HYDROGENATED TALLOW ALKYL) DI-		
METHYL, CHLORIDES, REACTION		
PRODUCTS WITH ATTAPULGITE (6.19%)		

## --- KEY TO LIST CITATIONS ---

1 = OSHA Z, 2 = ACGIH, 3 = IARC, 4 = NTP, 7 = NFPA 49,

8 = NFPA 325M, 9 = DOT HMT, 10 = CA RTK, 11 = IL RTK, 12 = MA RTK,

13 = MN RTK, 14 = NJ RTK, 15 = MI 293, 16 = FL RTK, 17 = PA RTK,

18 = CA P65.

--- NTP, IARC, AND OSHA INCLUDE CARCINOGENIC LISTINGS ---

NOTE: MOBIL PRODUCTS ARE NOT FORMULATED TO CONTAIN PCBS.

ក្នុងក្នុងក្នុងក្នុងក្នុងក្នុងក្នុងក្នុង	TS **********************
INGREDIENT DESCRIPTION	PERCENT CAS NUMBER
<>	<>   <>
CONTAINS THE FOLLOWING BASE OILS:	> 90.00
BASE OILS:	
LUBRICATING OILS (PETROLEUM), C>25	72623-83-7
HYDROTREATED BRIGHT STOCK-BASED	•
DISTILLATES (PETROLEUM), SOLVENT	64742-65-0
DEWAXED HEAVY PARAFFINIC	

## MODII

HOBILTEMP 78		640193-00	PAGE 5 OF 5
QUATERNARY AMMONIUM COMPOUNDS, BIS(HYDROGENATED TALLOW ALKYL) DIMETHYL, SALTS WITH BENTONITE	<	7.00	68953-58-2
1,2,3-PROPANETRIOL		1.25	56-81-5
MOLYBDENUM SULFIDE	<	1.00	1317-33-5
ZINC, BIS		0.25	15337-18-5
(DIPENTYLCARBAMODITHICATO- S,S')-, (T-4)-			
PHOSPHORIC ACID, TRISODIUM SALT		0.16	7601-54-9

FOR MOBIL USE ONLY: MHC: 1 1 NA 0 0, MPPEC: A, PPEC: A, US89-355
APPROVE CCODE: 7 11/27/90 REQ: US - MARKETING

INFORMATION GIVEN HEREIN IS OFFERED IN GOOD FAITH AS ACCURATE, BUT WITHOUT GUARANTEE. CONDITIONS OF USE AND SUITABILITY OF THE PRODUCT FOR PARTICULAR USES ARE BEYOND OUR CONTROL; ALL RISKS OF USE OF THE PRODUCT ARE THEREFORE ASSUMED BY THE USER AND WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. NOTHING IS INTENDED AS A RECOMMENDATION FOR USES WHICH INFRINGE VALID PATENTS OR AS EXTENDING LICENSE UNDER VALID PATENTS. APPROPRIATE WARNINGS AND SAFE HANDLING PROCEDURES SHOULD BE PROVIDED TO HANDLERS AND USERS.

PREPARED BY: MOBIL OIL CORPORATION

ENVIRONMENTAL HEALTH AND SAFETY DEPARTMENT, PRINCETON, NJ FOR FURTHER INFORMATION, CONTACT:

MOBIL OIL CORPORATION, PRODUCT FORMULATION AND QUALITY CONTROL 3225 GALLOWS ROAD, FAIRFAX, VA 22037 (800) 227-0707 X3265